



4K@60Hz DisplayPort to HDMI Cable

DisplayPort Male to HDMI Male Cable, 3 m (10 ft.), Black

Part No.: [153218](#)

The easiest and best way to connect a DisplayPort laptop or desktop to your HDMI display — in one complete cable

For the simplest and most discreet installation, this DisplayPort to HDMI cable connects your DisplayPort video source to the HDMI port on your display. It doesn't need a power source, unlike some converter dongles that require active power and separate bulky video cabling. This cable lets you enjoy movies on a big-screen HDTV, extend your desktop to a second monitor (up to 4K@60Hz) for an expanded workspace or show presentations on a projector at school or work without needing any other adapter or converter.

Features:

- Connects your DisplayPort source to your HDMI-equipped Ultra-HD display
- Supports Ultra-HD video resolution up to 4K@60Hz (3840 x 2160 @ 60Hz)
- Supports High-Definition audio for a full range of audio types, including SACD, DVD-Audio, DTS-HD Master Audio, and Dolby TrueHD
- Supports Ultra-HD video resolution up to 4K@60Hz (3840 x 2160 at 60 Hz) and High-Definition audio for a full range of audio types, including SACD, DVD-Audio, DTS-HD Master Audio, and Dolby TrueHD
- HDCP compatible for protected content
- Offers a latching DisplayPort connector to provide a secure connection
- Converts a signal from DisplayPort source to an HDMI display only; not bi-directional
- Plug-and-Play
- Three-year warranty

Specifications:

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com. All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Standards and Certifications

- DisplayPort v1.2
- FCC
- CE
- RoHS
- HDCP

General

- Resolution: up to 3840 x 2160 at 60 Hz (Ultra-HD 4K@60Hz)
- Converts signal from DisplayPort to HDMI only

Connectors

- DisplayPort 20-pin male (latching)
- HDMI 19-pin male
- Gold-plated contacts

Physical

- Length: 3 m (10 ft)
- Weight: 140 g (4.9 oz.)
- Molded PVC and ABS Shell

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- Windows XP/Vista/7/8.1/10, Linux or Mac 9.x/10.x or above

Package Contents

- 4K@60Hz DisplayPort to HDMI Cable



