



2 Port HDMI 10.2G Splitter, Compact

No.: 38357

Compact 2-way splitter for connecting one HDMI source device to two HDMI displays or projectors.

Description

- Connects a single 4K HDMI source to two 4K Ultra HD HDMI displays
- Supports resolutions up to 4K 3840x2160 @30Hz
- Supports HDMI audio pass-through
- USB powered for easy and discreet installation
- 2 year warranty

The Lindy 2 Port HDMI 10.2G Splitter is a compact, low cost solution for easily splitting one 4K HDMI source device across two 4K HDMI displays.

With support for resolutions up to 4K 3840x2160 @30Hz, content be viewed in superior clarity across dual displays. The splitter's compact design and ability to be powered by USB allows for a simple and discreet installation into a variety of environments, from home entertainment setups to office use.

Technical details

Specifications

- AV Interface: HDMI
- Interface Standard: HDMI 1.4
- Supports Bandwidth: 10.2Gbps
- Maximum Resolution: 3840x2160@30Hz 4:4:4 8bit
- HDCP Support: 1.4
- Supported Audio: Audio Pass-through
- Separate Audio Ports: -
- CEC Support: -
- Serial Interface: -
- Special Features: -

Connectors

- Input: HDMI Type A (Female)
- Output: 2 x HDMI Type A (Female)

- Control: -
- Power: 3.5/1.35mm

Physical Properties

- Dimensions (approx.) WxDxH: 76x48x16.5mm (2.99x1.89x0.65in)
- Housing Material: Plastic
- Net Weight: 0.039kg (0.09lb)
- Operating Temperature: 0°C - 70°C (32°F - 158°F)
- Storage Temperature: -10°C - 80°C (14°F - 176°F)
- Humidity: 10% to 85% RH (no condensation)
- Power Requirements: 5VDC 3.5A
- Colour: Black

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 145x107x50mm (5.71x4.21x1.97in)
- Gross Weight: 0.103kg (0.23lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH & California Proposition 65

Package Contents

- 2 Port HDMI 10.2G Splitter
- USB to DC Cable, 1m
- Lindy Manual

Purchasing Information

- No.: 38357
- EAN: 4002888383578