ENHANCED FOR EFFICIENCY



FFATURES

3rd Generation Dual Chamber Pump – Newly designed dual chamber pump for improved overall cooling efficiency and performance.

Enlarged Cooling Surface Area – Increased surface area on the radiator for better heat dissipation and enhanced cooling performance

New SickleFlow 120 RGB Fan – Improved lighting and performance using Air Balance fan blades, with new refreshed exterior design.

Reinforced Sealing – Using unique formula from high Industrial Grade EPDM material to increase the lifespan and reinforce the sealing to prevent leakage

RGB Lighting Solution – Fully customizable RGB lighting that is certified compatible with all major motherboard manufacturers (Wired Controller also included).

PACKING INFORMATION

EAN code	4719512095591
UPC code	884102067891
Net weight	1.34 kg
Gross weight	1.98 kg
Package dimension (L x W X H)	327 x 235 x 139 mm
Carton dimension (L x W x H)	585 x 345 x 270 mm
Units/CTN	4

П	Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
ľ	20′	1728	48	N/A
	40′	3648	48	N/A
Γ	40 HQ	4104	54	N/A

The Perfect Start

CoolerMaster MasterLiquid ML240L RGB V2 is a refreshed design from the popular MasterLiquid Lite Series that elevates the exterior design elements. The Pump of the ML240L RGB V2 has been enhanced with the newly designed 3rd Gen. Dual Chamber Pump that improves the overall cooling efficiency of the AIO water cooler. The radiator surface area has been enlarged to increase the surface area for heat dissipation for optimized cooling performance. The ML240L RGB V2 will included the latest SickleFlow 120 RGB fan with a brand new design and Air Balance fan blades that is quieter than before without compromising on air flow and pressure.

SPECIFICATIONS

Product Number MLW-D24M-A18PC-R2			MasterLiquid ML240L V2 RGB	
Intel			MLW-D24M-A18PC-R2	
CPU Socket			Black	
AMD	CPII Socket	Intel	1150 / 1155 / 1156	
Radiator Dimensions (L x W x H) inch) 277 x 119.6 x 27.2mm(10.9 x 4.7 x 1.1 inch) Pump Dimensions (L x W x H) inch) 79.9 x 76 x 47.1mm(3.1 x 3 x 1.9 inch) MTTF (Hours) 70,000 hours Noise Level (dBA) <15dBA	CI O SOCKET	AMD		
Dimensions (L x W x H)	D 11 1	Material	Aluminum	
Noise Level (dBA) 79.9 x 76 x 47.1mm(3.1 x 3 x 1.9 inch)	Radiator	(L x W x H)	`	
Noise Level (dBA) <15dBA			79.9 x 76 x 47.1mm(3.1 x 3 x 1.9 inch)	
Pump Connector 3-Pin Rated Voltage (VDC) 12		MTTF (Hours)	70,000 hours	
Connector 3-Pin	Division	Noise Level (dBA)	<15dBA	
(VDC) 12 Power Consumption (W) 2.36 W (LED 2.21W) Dimensions (L x W x H) 120 x 120 x 25mm (4.7 x 4.7 x 1 inch) Quantity (pcs) 2 LED Type RGB Speed (RPM) 650~1800RPM±10% Airflow (CFM) 62 CFM (Max) Noise Level (dBA) 8~27 dBA Pressure (mH2O) 2.5 mmH₂O (Max) Life Expectancy (Hours) 160,000 hours Power Connector 4-Pin Rated Voltage (VDC) 12 Rated Current (A) 0.15A (LED 0.2A) TDP (W) 200 W RAM Clearance N/A	Pump	Connector	3-Pin	
Consumption (W) 2.36 W (LED 2.21W)			12	
Dimensions (L x W x H) 120 x 120 x 25mm (4.7 x 4.7 x 1 inch) Quantity (pcs) 2 LED Type RGB Speed (RPM) 650~1800RPM±10% Airflow (CFM) 62 CFM (Max) Noise Level (dBA) 8~27 dBA Pressure (mmH20) 2.5 mmH₂O (Max) Life Expectancy (Hours) 160,000 hours Power Connector 4-Pin Rated Voltage (VDC) 12 Rated Current (A) 0.15A (LED 0.2A) TDP (W) 200 W RAM Clearance N/A			2.36 W (LED 2.21W)	
LED Type RGB Speed (RPM) 650~1800RPM±10% Airflow (CFM) 62 CFM (Max) Noise Level (dBA) 8~27 dBA Pressure (mmH2O) 2.5 mmH ₂ O (Max) Life Expectancy (Hours) 160,000 hours Power Connector 4-Pin Rated Voltage (VDC) 12 Rated Current (A) 0.15A (LED 0.2A) TDP (W) 200 W RAM Clearance N/A		Dimensions	120 x 120 x 25mm (4.7 x 4.7 x 1 inch)	
Speed (RPM) 650~1800RPM±10%		Quantity (pcs)	2	
Airflow (CFM) 62 CFM (Max) Noise Level (dBA) 8~27 dBA Pressure (mmH2O) Life Expectancy (Hours) 160,000 hours Power Connector 4-Pin Rated Voltage (VDC) Rated Current (A) 0.15A (LED 0.2A) TDP (W) 200 W RAM Clearance N/A		LED Type	RGB	
Fan Noise Level (dBA) 8~27 dBA Pressure (mmH2O) Life Expectancy (Hours) Power Connector 4-Pin Rated Voltage (VDC) Rated Current (A) 0.15A (LED 0.2A) TDP (W) RAM Clearance N/A		Speed (RPM)	650~1800RPM±10%	
Pressure (mmH2O) Life Expectancy (Hours) Power Connector Rated Voltage (VDC) Rated Current (A) TDP (W) RAM Clearance 2.5 mmH ₂ O (Max) 160,000 hours 12 12 200 W		Airflow (CFM)	62 CFM (Max)	
(mmH2O) Life Expectancy (Hours) Power Connector Rated Voltage (VDC) Rated Current (A) TDP (W) RAM Clearance 2.5 mmH₂O (Max) 160,000 hours 120,000 hours 12 200 w	Fan	Noise Level (dBA)	8~27 dBA	
(Hours)			2.5 mmH₂O (Max)	
Rated Voltage (VDC) 12			160,000 hours	
(VDC) 12 Rated Current (A) 0.15A (LED 0.2A) TDP (W) 200 W RAM Clearance N/A		Power Connector	4-Pin	
TDP (W) 200 W RAM Clearance N/A			12	
RAM Clearance N/A		Rated Current (A)	0.15A (LED 0.2A)	
	TDP (W)		200 W	
W	RAM Clearance		N/A	
warranty 2 years	Warranty		2 years	



FEATURES







New Dual Chamber Pump

3rd Generation dual chamber pump designed for better performance and overall efficiency. Larger Surface Area

Increased surface area of the fins on the radiator for better heat dissipation. **RGB** Ready

Refresh of the Masterliquid Lite comes in RGB allowing you to control the color mood of you build. Certified compatible with all major motherboard manufacturers'.



Wired Controller Included

Perfect starter kit for those whom do not have RGB ports



Reinforced Sealing

Improved manufacturing process which will increase the lifespan of your cooler and also prevent leaking.



SickleFlow 120 RGB

New SickleFlow 120 RGB with improved performance and new exterior outlook