

Product Highlights

Full-Resolution Video

HDMI video up to 4K @ 30 Hz Ultra HD resolution for stunning videos and images with no lag

Ultra-Fast USB 3.0

SuperSpeed USB 3.0 technology allows you to transfer files up to 10 times faster than with USB 2.0

Dual-Slot SD Card Reader

Dual-slot SD card reader is compatible with both SD and microSD cards



DUB-M530

5-in-1 USB-C Hub with HDMI/Card Reader

Features

HDMI Compatibility

- Ultra HD video resolution up to 4K @ 30 Hz
- Supports HDMI 1.4 and DisplayPort Alternate Mode over USB-C
- HDCP 2.2 compatible

SD Card Compatibility

- SD card & microSD card
- v1.0/v2.0 (SDHC)/v3.0 (SDXC)

USB Type-C with Simple Installation

- Two USB 3.0 SuperSpeed 5 Gbps ports
- Backwards compatible with USB 2.0 and USB 1.1
- Simply plug-and-play, no software required

Sturdy Aluminum Casing

- Strong aluminum alloy casing

The DUB-M530 5-in-1 USB-C Hub with HDMI/Card Reader allows you to instantly add a second display, a SD card reader, and two additional USB 3.0 ports to your ultra-portable computer. Just plug the DUB-M530 into an available USB Type-C port and you're ready to send content to your TV or monitor in full resolution with the reliability of a wired video connection. You can also connect up to 2 more USB devices, as well as insert a microSD or regular SD card, giving you direct access to your full-resolution photos stored on memory cards from your cameras.

Hardware Overview



DUB-M530 5-in-1 USB-C Hub with HDMI/Card Reader

Technical Specifications

Connectivity

Device Interfaces	<ul style="list-style-type: none">• HDMI Port (3840 x 2160 or 4096 x 2160 pixels @ 30 Hz)• MicroSD card slot• SD card slot	<ul style="list-style-type: none">• Two USB 3.0 Type-A Ports• USB Type-C Connector (Thunderbolt 3 compliant)
Standards	<ul style="list-style-type: none">• USB Specification Version 3.0• USB Specification Version 2.0• USB Specification Version 1.1• SD card v1.0/v2.0 (SDHC)/v3.0 (SDXC)	<ul style="list-style-type: none">• HDMI 1.4• HDCP 2.2• DisplayPort Alternate Mode

General

Minimum System Requirements	<ul style="list-style-type: none">• Computer running Microsoft Windows, Mac OS, or Chrome OS	<ul style="list-style-type: none">• A USB Type-C Port with DisplayPort Alternate Mode support
-----------------------------	--	---

Physical

Dimensions (W x H x D)	<ul style="list-style-type: none">• 96 x 29 x 9 mm	<ul style="list-style-type: none">• Cable length: 11.5 cm
Weight	<ul style="list-style-type: none">• 42.0 g	
Power	<ul style="list-style-type: none">• Input: Bus-powered	<ul style="list-style-type: none">• Consumption: 131 mA, 5 V DC
Temperature	<ul style="list-style-type: none">• Operating: 0 to 70 °C (32 to 158 °F)	<ul style="list-style-type: none">• Storage: -25 to 85 °C (-13 to 185 °F)
Humidity	<ul style="list-style-type: none">• Operating: 5% to 80% RH, non-condensing	<ul style="list-style-type: none">• Storage: 5% to 80% RH, non-condensing
Certifications	<ul style="list-style-type: none">• CE• IC	<ul style="list-style-type: none">• FCC• RCM



For more information: www.dlink.com

D-Link European Headquarters. D-Link (Europe) Ltd., First Floor, Artemis Building, Odyssey Business Park, West End Road, South Ruislip HA4 6QE, United Kingdom.
Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners. ©2019 D-Link Corporation. All rights reserved. E&OE.

Updated September 2019

D-Link[®]