

AXIS C1310-E Network Horn Speaker

Outdoor speaker for clear long-range speech

AXIS C1310-E Network Horn Speaker is perfect for outdoor environments in most climates. It allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. Built-in memory supports pre-recorded messages, or security personal can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP). AXIS C1310-E is a standalone unit that can be placed almost anywhere, which supports a flexible, scalable and cost-effective approach to system design.

- > [All-in-one speaker system](#)
- > [Connects to standard network](#)
- > [Simple installation with PoE](#)
- > [Remote health testing](#)
- > [Two input/outputs \(GPIO\)](#)



AXIS C1310-E Network Horn Speaker

Audio hardware	
Enclosure	One way enclosure with 2.5 inches broadband dynamic cone speaker
Max sound pressure level	>121 dB
Frequency response	280 Hz - 12.5 kHz
Coverage pattern	70° horizontal by 100° vertical (at 2 kHz)
Audio input/output	Built-in microphone (can be disabled mechanically)
Built-in microphone specification	50 Hz - 12 kHz
Digital signal processing	Built-in and pre-configured
Amplifier description	Built-in 7 W Class D amplifier
Audio management	
AXIS Audio Manager Edge	Built in: – Content management for music and live/pre-recorded announcements. – Scheduling to decide when and where to play specific content. – Content prioritization to ensure urgent messages interrupt the schedule. – Zone management allowing you to divide up to 200 speakers into 20 zones. – Health monitoring for remote discovery of system errors. – User management to control who has access to what features. See separate datasheet for more details.
AXIS Audio Manager Pro	For larger and more advanced systems. Sold separately. See separate datasheet for specifications.
Audio software	
Audio streaming	One-way/two-way with optional half-duplex echo cancellation. Mono.
Audio encoding	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Axis μ -law 16 kHz, WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Constant and variable bit rate. Sampling rate from 8 kHz up to 48 kHz.
System on chip (SoC)	
Model	i.MX 6ULL
Memory	256 MB RAM, 512 MB Flash
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log
Network protocols	IPv4/v6, HTTP, HTTPS ^a , SIP, SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, TCP, UDP, IGMPv1/v2/v3, ICMP, DHCP, ARP, SOCKS, SSH
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] , One-click cloud connection, AXIS Camera Application Platform (ACAP).
VoIP	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX. Tested with: SIP client such as Cisco, Bria and Grandstream and PBX suppliers such as Cisco and Asterisk.
Intelligent audio	Auto Speaker Test
Event triggers	Virtual inputs, External input Call: DTMF, State changes, AXIS Camera Application Platform (ACAP)
Event actions	File upload: HTTP, network share and email Notification: email, HTTP and TCP Play audio clip Perform Auto Speaker Test Send SNMP trap Status LED
Built-in installation aids	Test tone verification and identification
Functional monitoring	Auto Speaker Test, Connection verification, Built-in system logging
General	
Casing	Impact-resistant aluminum, IP66-, IP67-, NEMA 4X-rated, and MIL-STD-810G 509.5-rated.
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 (max. 12.95 W)
Connectors	RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block for one input and one output
Reliability	Designed for 24/7 operation.
Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Humidity 5-95% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10-100% RH (condensing)
Approvals	EMC EN 55032 Class B, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), VCCI Class B, RCM AS/NZS CISPR 32 Class B, KC KN32 Class B, KC KN35 Safety CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 60950-22 Environment IEC/EN 60529 IP67, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, NEMA 250 Type 4X, MIL-STD-810G 509.5
Dimensions	Ø182 X 52 mm (7.2 x 2.1 in)
Weight	1.3 kg (2.9 lb.)
Included accessories	Installation Guide, AVHS Authentication Key, AXIS Camera Station license key, AXIS Connector Guard A, Cable shoe
Optional accessories	AXIS T91B47 Pole Mount, AXIS T91F67 Pole Mount, Cable Gland M20x1.5, RJ45, Cable Gland A M20, AXIS Power over Ethernet Midspans, T94R01B Corner Bracket, T94P01B Corner Bracket, T94S01P Conduit Back Box For more accessories, see axis.com
Video management software	AXIS Camera Station, AXIS Companion, Video management software from Axis' Application Development Partners available on axis.com/techsup/software
Languages	English, German, French, Spanish, Italian
Warranty	5-year warranty, see axis.com/warranty

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).