

# AXIS Q6100-E Network Camera

## For 360° real-time monitoring and great detail

With four 5 MP sensors, AXIS Q6100-E provides a complete 360° overview with great image usability day and night. Designed for use with any AXIS Q61 Series or AXIS Q63 Series camera, it enables one-click PTZ control and autopilot for automatic PTZ tracking within the viewing areas. Directional audio detection triggered by audio incidents redirects the PTZ camera to the audio source. Each sensor has exchangeable lenses with autofocus for maximum flexibility and accurate configuration. AXIS Camera Heater Power Supply is required when AXIS Q6315-LE is used.

- > 360° camera with one-click PTZ control
- > 4 x 5 MP sensors, total 20 MP resolution
- > Exchangeable and tiltable lenses
- > Requires an AXIS Q61 Series or AXIS Q63 Series camera
- > Directional audio detection included



# AXIS Q6100-E Network Camera

Models	AXIS Q6100-E 50 Hz AXIS Q6100-E 60 Hz	Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset Overlay text, day/night mode, Status LED, WDR mode MQTT publish
<b>Camera</b>		Data streaming	Event data
Supported products	AXIS Q61-E PTZ Network Cameras AXIS Q63-E PTZ Network Cameras	Built-in installation aids	Installation focus, lens selection, positioning calibration, PTZ remote connection
Image sensor	4 x 5 MP progressive scan RGB CMOS 1/2.5"	<b>General</b>	
Lens	Autofocus lenses, Fixed iris, F2.0, Focal length: 2.8 mm Horizontal field of view: 360° Vertical field of view: 84°	Casing	IP66-, NEMA 4X- and IK10-rated Polycarbonate hardcoated dome Aluminum casing
Day and night	Automatically removable infrared-cut filter	Sustainability	PVC free
Minimum illumination	Color: 0.4 lux at 50 IRE, F2.0 B/W: 0.03 lux at 50 IRE, F2.0	Power	<b>AXIS Q6100-E with Solo Kit (without a PTZ):</b> Power consumption: typical 9 W, max 23 W External power input 24 V DC: typical 8.6 W, max 75 W AXIS Midspan 30 W 1-port: 100-240 V AC, max. 30 W <b>AXIS Q6100-E with AXIS Q61-E PTZ Network Cameras:</b> AXIS High PoE midspan 1-port 100-240 V AC, max 60 W recommended <b>AXIS Q6100-E with AXIS Q63-E PTZ Network Cameras:</b> AXIS High PoE midspan 1-port 100-240 V AC, max 60 W recommended, plus AXIS Camera Heater Power Supply (required when used with AXIS Q63-E PTZ Network Camera)
Shutter speed	1/32500 to 1/20 s	Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE RJ45 10BASE-T/100BASE-TX/1000BASE-T Q61-E port M8 3-pin AC/DC input
Camera angle adjustment	Pan, tilt and rotate	Storage	Support for SD/SDHC/SDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
Pan/Tilt/Zoom	One-click PTZ control	Operating conditions	-50 °C to 50 °C (-58 °F to 122 °F) with AXIS Camera Heater Power Supply -40 °C to 50 °C (-40 °F to 122 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Start-up temperature: -40 °C (-40 °F) Humidity 10–100% RH (condensing)
<b>System on chip (SoC)</b>		Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Model	S5	Approvals	<b>EMC</b> EAC, EN 55032 Class A, EN 55035, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KN35 <b>Safety</b> IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 60950-22, CAN/CSA-C22.2 No. 60950-22, IS 13252 <b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9) <b>Network</b> NIST SP500-267
Memory	2048 MB RAM, 512 MB Flash	Dimensions	ø 361 mm (14.2 in) Height: 192 mm (7.6 in)
<b>Video</b>		Weight	4.0 kg (8.8 lb) excluding an AXIS Q61-E PTZ Network Camera or AXIS Q63-E PTZ Network Camera
Video compression	H.264 (MPEG-4 Part 10/AVC), Main and High Profile H.265 (MPEG-H Part 2/HEVC), Main Profile	Included accessories	AXIS Q61-E and AXIS Q63-E adapter, bayonet screws, installation guide, Windows® decoder 1-user license
Resolution	4 x 2592x1944 to 320x240 Default: 2592x1944	Required accessories	AXIS Camera Heater Power Supply is required when AXIS Q6315-LE is used.
Frame rate	Up to 20 fps (50/60 Hz) in all resolutions	Optional accessories	Axis Lens M12 6 mm 5P, Axis Lens M12 12 mm 5P, Axis Lens M12 16 mm 5P, Axis Lens M12 25 mm 5P, AXIS T91 Mounting accessories, Axis Midspan 60 W 1-port, AXIS Camera Heater Power Supply For more accessories, see <a href="http://axis.com">axis.com</a>
Video streaming	Multiple, individually configurable streams in H.264 and H.265 Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265	<b>System integration</b>	
Image settings	Resolution, compression, saturation, brightness, sharpness, contrast, white balance, exposure level, exposure mode, shutter & gain fine tuning of behavior at normal and low light, polygon privacy masks (maximum 8 per channel), WDR, dynamic text and image overlay	Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> One-click cloud connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S, and ONVIF® Profile T, specification at <a href="http://onvif.org">onvif.org</a>
<b>Network</b>		Analytics	<b>Included</b> Directional audio detection, autopilot, AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard, AXIS Video Motion Detection, active tampering alarm, edge storage events Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
Security	Password protection, IP address filtering, HTTPS encryption, IEEE 802.1x (EAP-TLS) network access control, digest authentication, user access log, centralized certificate management, brute force delay protection	Event conditions	Analytics, edge storage events, virtual inputs through API Device status: above operating temperature, above or below operating temperature, below operating temperature, fan failure, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: manual trigger, virtual input MQTT subscribe PTZ: PTZ ready Scheduled and recurring: scheduled event Video: day-night mode, live stream open, tampering
Network protocols	IPv4, IPv6, USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, HTTP/2, TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SSH, NTCIP, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)		

Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="https://axis.com/vms">axis.com/vms</a>	Warranty	5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>	