



V7 UPS 600VA Desktop UPS

UPS1P600E

SKU: CA08356

The 600VA Desktop UPS by V7 protects your electronic equipment from damage due to power outages, surges and spikes while providing short term battery power during an outage. Featuring Automatic Voltage Regulation (AVR), which instantly adjusts high and low voltages to safe levels for your electronics, so you can work indefinitely through sustained fluctuations. Specifically designed to protect your equipment and network connection in harsh power environments, the 600VA Deskop UPS ensures maximum productivity and work efficiency.

- LCD Indicator and Audible Status Alarms
- Automatic Voltage Regulation (AVR) instantly corrects voltage fluctuations
- 4 battery backup and surge protected IEC C13 outlets
- Includes: UK and EU Power Cords and two IEC320 C14 (M) to C13 Cables

General

Sku: CA08356
 Model: UPS1P600E
 EAN: 0662919109337
 Warranty: 3 Year (1 Year Battery)
 Compliance: CE, REACH, RoHS
 Country Of Origin: China
 Package Type: 4 Color Box
 SAP: 4938673
 Package Includes: 2 IEC-IEC cables & (EU/UK) power cables, USB Cable, user's manual, warranty and compliance docs

Color

Color: Black

Design

UPS Style: Desktop

Other

Assurance: up to 75.000 € connected equipment assurance
 Software: ViewPower for viewing, controlling, and monitoring your UPS systems and automatic computer shutdown. Shutdown Wizard for standalone software allowing automatic computer shutdown

Package Dimensions

Package Dimensions (L/W/H): 344 x 140 x 220 mm
 Shipping Weight: 4.8kg

Product Dimensions

Product Dim (L/W/H): 300 x 101 x 142 mm
 Product Weight: 4.2kg

Technical

Voltage: 220/230/240 VAC
 Battery Type: Sealed Lead Acid
 Outlets: 4 Outlets
 Input AC Plug Type: BS 1363 (UK), Schuko (EU)
 Communication/Configuration Ports: USB
 Load Capacity (Watts): 360W
 Load Capacity Volt Amp (VA): 600VA
 Noise Level: Less than 40 dB
 Audible Alarms: Voltage, Load Level, Battery Low, Overload
 Category: Line Interactive
 Recharge Time: 4-6 hours recover to 90% capacity
 Transfer Time: Typical 2-6ms (max 10ms)
 Waveform Type: Simulated Sine Wave
 Backup Runtime: 5 minutes @ half load
 Frequency Range: 50/60Hz Auto-Sensing
 LED status light: AC Mode (Green), Battery (Flashing Yellow)
 Surge Protection: 312 Joules
 Visual Indicator: Touch LCD: AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload, Fault and Low Battery
 Output Voltage, Overload, Fault and Low Battery
 Battery Volt Amp Hour Capacity: 12V/7Ah
 Data Line Protection: RJ-11
 AC Cord length: 1.5m



Specifications

See next page

**INPUT**

Acceptable Voltage Range 180 - 270 VAC

OUTPUT

Voltage 230 VAC

AC Voltage Regulation (Batt. Mode) $\pm 10\%$

BATTERY

Battery Type & Number 12 V/7Ah x 1

ALARM

Battery Mode Sounds every 10 seconds

Low Battery Sounds every second

Overload Sounds every 0.5 seconds

Fault Continuously sounds

PROTECTION

UPS System Protection Overload, discharge, and overcharge

ENVIRONMENT

Humidity 0-90 % RH @ 0- 40°C (non-condensing)