

PT-FRZ60 Series

1-Chip DLP™ Projectors

AVAILABLE FROM SEPTEMBER 2020

Easy-to-Manage 1-Chip DLP™ Laser Projectors Offer Clear Pictures in Bright Rooms with Flexible Integration in the Classroom or Office



PT-FRZ60/FRZ50
Black model also available.



PT-FRZ55



PT-FRZ60 Series			
	PT-FRZ60	PT-FRZ50	PT-FRZ55
Light Output	6,000 lm* ¹ /6,200 lm (Center)* ²	5,200 lm* ¹ /5,400 lm (Center)* ²	5,000 lm* ¹ /5,200 lm (Center)* ²
Resolution	WUXGA		

• *Dynamic Images in Bright Rooms with Silent Operation*

No more dark rooms and distracting projector noise. PT-FRZ60 Series creates dynamic images that resist washout under lights while operating noise is reduced to an inaudible 27 dB³ in Quiet Mode. Quartet Color Harmonizer optimizes wheel and filter to boost color vibrancy.

• *Compact, Lightweight Projectors are Easy to Install*

Projectors feature a 2.0x optical zoom⁴ to increase throw-distance range for flexible installation, while 4K signal input⁵ via CEC-compatible HDMI® and DIGITAL LINK smooths integration with the latest infrastructure. Separate LAN and 5 V/2 A USB outlet support wireless projection.

• *Proven SOLID SHINE Laser Reliability*

The PT-FRZ60 Series features a high-efficiency filterless cooling system, hermetically sealed DMD block, and dust-resistant shielded laser drive to assure 20,000 hours⁶ of stable maintenance-free projection. A linear brightness ramp and strong color retention preserve image quality for longer.

*¹ Measurement, measuring conditions (TBD), and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. *² Average light-output value of all shipped products measured at center of screen in NORMAL Mode. *³ FRZ50/FRZ55 only (TBD). FRZ60 operates at 30 dB in Quiet Mode (TBD). *⁴ Excluding the PT-FRZ55. *⁵ 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI®. *⁶ Around this time, light output will have decreased by approximately 50%. IEC62087: 2008 Broadcast Contents, NORMAL Mode, Dynamic Contrast [ON], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. Estimated time until brightness decreases to 50% will vary depending on environment and usage conditions. Parts other than the light source may require replacement before 20,000 hours, and checkup is recommended around this time.

Specifications (Tentative)

Model	PT-FRZ60	PT-FRZ50	PT-FRZ55
Projector type	1-Chip DLP™ projector		
DLP™ chip	Panel size	17.0 mm (0.67 in) diagonal (16:10 aspect ratio)	
	Display method	DLP™ chip x 1, DLP™ projection system	
	Number of pixels	2,304,000 (1920 x 1200 pixels)	
Light source	Laser diodes		
Light output	6,000 lm ¹ /6,200 lm (Center) ²	5,200 lm ¹ /5,400 lm (Center) ²	5,000 lm ¹ /5,200 lm (Center) ²
Time until light output declines to 50 % ³	20,000 hours (NORMAL)		
Resolution	1920 x 1200 pixels		
Contrast ratio ⁴	20,000:1 (Full On/Full Off, Dynamic Contrast Mode: ON)		
Screen size [diagonal]	1.02–7.62 m (40–300 in), 16:10 aspect ratio		
Center-to-corner zone ratio ⁴	90 %		
Lens	2.0x manual zoom (throw ratio: 1.46–2.94:1), manual focus, F 2.0–3.4, f 21.5–43.0 mm		Fixed (throw ratio: 0.8:1), powered focus, F 1.75, f 11.9 mm
Lens shift (From the origin point of the lens mounter)	Vertical	+64 %, -44 % (manual)	
	Horizontal	+34 %, -27 % (manual)	
Keystone correction range	Vertical: ±40 °, Horizontal: ±20 °. When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of ±60 °.		Vertical: ±25 °, Horizontal: ±20 °. When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of ±45 °.
Installation	Ceiling/floor, front/rear, free 360-degree installation		
Terminals	HDMI® IN	HDMI 19-pin x 2 (Compatible with HDCP 2.2, Deep Color, 4K/60p signal input ⁴), CEC supported	
	COMPUTER 1 IN	D-sub HD 15-pin (female) x 1 (RGB/YPbPr/YCbCr/YC)	
	COMPUTER 2 IN/1 OUT	D-sub HD 15-pin (female) x 1 (RGB/YPbPr/YCbCr/YC)	
	VIDEO IN	Pin jack x 1 (composite video)	
	AUDIO IN 1	Pin jack x 2 (L, R)	
	AUDIO IN 2/3	M3 x 1/M3 x 1	
	AUDIO OUT	M3 x 1 (Variable)	
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)	
	DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connections (HDBaseT™ compliant), PJLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible, 4K/60p signal input ⁴	
	LAN	RJ-45 x 1 for network connection, PJLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible	
USB	USB connector (Type A) x 1 (Output 5 V/2 A)		
Power supply	AC 100–240 V, 50/60 Hz		
Power consumption	TBD		
Cabinet materials	Molded plastic		
Operation noise ⁵	30 dB (Quiet Mode) (TBD), 35 dB (Normal Mode) (TBD)	27 dB (Quiet Mode) (TBD), 32 dB (Normal Mode) (TBD)	
Dimensions (W x H x D)	498 x 168 ⁶ x 492 mm (19 5/8" x 6 5/8" x 19 3/8")		498 x 168 ⁶ x 481 mm (19 5/8" x 6 5/8" x 18 15/16")
Weight ⁶	Approx. 16.6 kg (36.6 lbs) (TBD)		Approx. 16.3 kg (35.9 lbs) (TBD)
Operating environment	Operating temperature: 0–40 °C (32–104 °F), operating humidity: 10–80 % (no condensation) (TBD)		Operating temperature: 0–45 °C (32–113 °F), operating humidity: 10–80 % (no condensation) (TBD)
	Applicable software		
	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software		

¹ Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. ² Average light-output value of all shipped products measured at center of screen in NORMAL Mode. ³ Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, NORMAL Mode, Dynamic Contrast (ON), under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m³ of particulate matter. Estimated time until light output declines to 50 % varies depending on environment. ⁴ 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI®. ⁵ With legs at shortest position. ⁶ Average value. May differ depending on the actual unit.

Optional Accessories

- **Ceiling Mount Bracket**
ET-PKD120H* (for high ceiling)
ET-PKD120S* (for low ceiling)
* The ET-PKD120H/PKD120S are used in combination with the ET-PKD130B (sold separately).
- **Projector Mount Bracket**
ET-PKD130B
- **DIGITAL LINK Switcher**
ET-YFB200G
Note: ET-YFB200G is not compatible with 4K signals.
- **Digital Interface Box**
ET-YFB100G
Note: ET-YFB100G is not compatible with 4K signals.
- **Early Warning Software**
ET-SWA100/105
Note: Part number suffix may differ depending on the license type.
* Multi Monitoring & Control Software Ver. 2.0 or later is required.
Please download from the following website:
www.panasonic.net/cns/projector/download/application/
- **D-sub/S-VIDEO Conversion Cable**
ET-ADSV

Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability may vary by country or region. This product may be subject to export control regulations. DLP, DLP logo and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. Trademark PJLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. SOLID SHINE is a trademark of Panasonic Corporation. All other trademarks are the property of their respective trademark owners. © 2020 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
Projector Global Website – panasonic.net/cns/projector
Facebook – www.facebook.com/panasonicprojectoranddisplay
YouTube – www.youtube.com/user/PanasonicProjector

All information included here is valid as of February 2020.

PT-FRZ60PRE1 Printed in Japan.