

K
SERIES

, " ! - ! \$. / . ' # \$ % # ' .
O , * , ' 1 ## * ..

223.4.523.4.623.4.723.4.873



! " # \$ % &

' ! () * % ! +
B, / " 6, / " 4-

! " # \$ % & ' () * + # , # - \$. # / # - \$ 0 1 2 3 4 # (" 5 ' 6 ' / 7 8 - \$
superior visual clarity with seamless connectivity
9 # : 4 ;) # - \$ 4 ' \$ < # 6 , & #) \$: \$ (') = ') : 4 # \$) : 5 / # \$ ' 9 \$ < , - = 6 : 7 - \$
4 " : 4 \$:) # \$, < # : 6 9 ') \$. ' < #) 5 \$ > ') ? - = : (# - 4 3 # - , / 5 # < \$ 9 ') \$
versatility across corporate, educational, and public
settings, the K Series ranges from 55 to 98 inches,
5 - ;) , 5 / \$: \$ = #) 9 # (4 \$. : 4 (" \$ 9 ') \$: 5 7 \$ - = : (# 4

With advanced integration capabilities like wireless
- () # # 5 \$ - " :) , 5 / \$ 4 ") ' ; / " \$ A ' 5 4 : / # \$: 5 < \$ < , / 4 : 6 \$ - , / 5 : / # \$
via Rise Vision, the K Series stands as the ultimate
choice for organizations aiming to elevate their
visual communication and collaboration.

! " # \$ % & ' () * + # , # - \$ # 5 (: = - ; 6 : 4 # - \$ 4 " # \$ 9 ; 4 ;) # \$ ' 9 \$
professional displays, offering unmatched quality,
connectivity, and ease of use in one comprehensive
solution.



! " # \$ % & ' () * + , & (" - . / 0 & . ()
With sizes ranging from 55" to 98", the
K Series ensures a perfect fit for a wide
variety of use cases, from small huddle-
style meetings to expansive auditoriums,
6 # (4 ;) # \$ ' ' . - \$: 5 < \$! ' > 5 \$ B : 6 \$ - = : (# - 4



1 2 \$ &) / " (3 / . 2 * % (4 & - ") # * + 5 & ()
With 4K resolution featuring QLED and
HDR, the K Series features stunning visual
clarity, ensuring content is vibrant, vivid
: 5 < \$ # 5 / : / 5 / 4



1 ' 2 + + / + , (6) / , 7 ' + & . (* + 8 (! " % ' 2)
450 nits of high brightness and 90%
DCI-P3 for brilliant color accuracy, K Series
displays are even visible in well-lit areas,
> , 4 " \$: 6 6 4 7 = # - \$ ' 9 \$ (' 5 4 # 5 4 4



Comprehensive Connectivity
With multiple HDMI ports, USB-A, LAN,
and WiFi/Bluetooth support, the K Series
, - \$) # : < 7 \$ 9 ') \$: 5 7 \$, 5 = ; 4 \$ - ' ;) (# \$: 5 < \$ 5 # 4 > ') ? \$
configuration, making installation and
integration straightforward.

DisplayNote Montage



DisplayNote Montage x RiseVision
C # : 4 ;) , 5 / \$ A ' 5 4 : / # \$ 9 ') \$ - # : . 6 # - \$ >) # 6 # - \$ - \$
- " :) , 5 / \$: 5 < \$ D , - # \$ E , - , ' 5 \$ 9 ') \$ < 7 5 : . , (\$ < , / 4 : 6 \$
signage, transforms idle displays into hubs
of interactive team collaboration.

avocor

! " # \$ % & ' () * !

O% L(, B\$, " /M22N0	, " /M52N0	, " /M62N0	, " /M72N0	, " /M87N0
+F#	55"	65"	75"	85"	98"
Backlight	Direct-lit QLED				
Aspect Ratio	16:9				
Resolution	3840 x 2160 @ 60Hz				
D#-=' 5-#1, , #	≤ 7ms				
Brightness	450 (cd/m2)				
Contrast Ratio	1200:1				
E,#>,5/%5/#	178° / 178°				
+; ==')4#<4G' 6')-	10 Bit 1.07 Billion Color with 90% DCI-P3				
Operation Time	7 days x 16 hours				
Display Orientation	1:5<-(:=#				
Anti-Glare Glass	N/A	N/A	N/A	N/A	H#-
*!) - 1.' B' *#P					
I54#)9:(#	Non-Touch				
-L)					
CPU	A73*4				
GPU	Mali G52 MC1				
D%AJDKA	4G+32G				
%5<)' ,<48#)-.' 5	%5<)' ,<4LM				
-! ++#- *%#*%B	\$				
+,<#15=; 4-\$	HDMI 2.1, 1 x Type-C (15W PD), 1 x USB-A 3.0, 1 x USB-B 2.0				
%;<,'	1 x 3.5mm (LINE OUT)				
G' 54)' 6	1 x RJ45 LAN (100M) + RS232 (DB9 male)				
OPS Slot	No				
N,C,	WiFi 5 2.4GHz/5GHz + BT5.0				
,) O%#					
Built-in Speakers	2 x 10W Bottom Front			2 x 15W Bottom Front	
A,(0)' ='' 5#9%): 7	N/A				
G: . #):	N/A				
O% L(, B,K,\$#P! *#.#) + - *%# +'					
Auto-Source-Detection	H#-				
Image Settings	H#-				
L1B' %-, (' L#-90%- , *%# +'					
Screen Dimensions (L x W x H)	1232.4 x 83.6 x 713.7mm / 48.5 x 3.3 x 28 inches	1451.4 x 83.9 x 835.7 mm / 57.1 x 3.3 x 32.9 inches	1673.4 x 87 x 964.5mm / 65.8 x 3.4 x 37.9 inches	1894 x 101 x 1097mm / 74.5 x 3.9 x 43.1 inches	2181.6 x 110.6 x 1246.7mm / 85.9 x 4.3 x 49.1 inches
Bezel Dimensions	4.5 x 4.5 x 4.5 x 20.6mm / 0.18 x 0.18 x 0.18 x 0.81 inches	5.3 x 5.3 x 5.3 x 19.3mm / 0.21 x 0.21 x 0.21 x 0.76 inches	4.6 x 4.6 x 4.6 x 19.3mm / 0.18 x 0.18 x 0.18 x 0.76 inches	3.5 x 3.5 x 3.5 x 20.4mm / 0.13 x 0.13 x 0.13 x 0.80 inches	3.5 x 3.5 x 3.5 x 19.4mm / 0.13 x 0.13 x 0.13 x 0.76 inches
Shipping Dimensions (L x W x H)	1350 x 152 x 837mm / 53.1 x 5.9 x 32.9 inches	1600 x 178 x 960mm / 62.9 x 7.0 x 37.7 inches	1840 x 230 x 1103mm / 72.4 x 9.0 x 43.4 inches	2050 x 230 x 1280mm / 80.7 x 9.0 x 50.3 inches	2390 x 280 x 1500mm / 94.1 x 11 x 59.1 inches
Weight (Net)	14.5kg / 31.9 lbs	20.1kg / 44.3 lbs	29.3kg / 64.6 lbs	38.6kg / 85.1 lbs	59kg / 130.1 lbs
Weight (Gross)	18.8kg / 41.4 lbs	26.6kg / 58.6 lbs	41.2kg / 90.8 lbs	52kg / 114 lbs	86.5kg / 190 lbs
Wall Mount (VESA)	400 x 300	400 x 300	400 x 300	500 x 200	800 x 400
IPC Mount	None				
L! &#;\$					
Max Power Consumption	180W	230W	280W	340W	475W
#+' %\$! +P#+' , (
Operating Temperature	0-40°C, 10-90% RH non-condensing				
+4') :/#1# . =#):4;)#	-20-60°C, 10-90% RH non-condensing				
B: . ,<47	See above				
& 1, *, -! P#* %+. *1#.#! R					
1.5m power cord (region specific), 1 x Tabletop stand, Remote control w/batteries, Wall Mount Bracket*					
&, \$\$, +*B					

Terms and conditions vary via region, please [click here](#)

A) B.%* .&%* 1

Upgrade your solution with:

>>>>DEFE=FEFEG



9.: : <> <=> ?>



, HI @ = , - J : < ? . K . L = E @ F @



, DEFE = . PESIJ : ! @ < ? U